

C5300 COLOUR AND MONO PRINTER



❖❖❖ C5300n ❖❖❖ C5300dn

FAST COLOUR AND MONO ON ONE AFFORDABLE PRINTER

The C5000 Series enables individuals in business and small workgroups to print in colour and mono without waiting and without paying extra for the privilege. With these professional office printers you can print stationery, proposals, short-run mailers and even 1.2m long banners and booklets. The C5300 are powerful network printers that accommodate 2-4 users in a small workgroup, but depending on the volume of printing, will comfortably serve more.

MAIN FEATURES OF THE C5300n AND C5300dn

- ❖❖❖ 12 pages per minute (ppm) full colour and 20ppm mono
- ❖❖❖ Time to first print 14 seconds colour, 9 seconds mono
- ❖❖❖ Resolution 600 x 1200 dpi
- ❖❖❖ 400MHz processor with 124MB RAM (64MB on C5300n)
- ❖❖❖ PCL5c and PostScript® 3 emulations as standard
- ❖❖❖ LED technology delivers high speed and superb reliability
- ❖❖❖ Compact stylish design in a small footprint
- ❖❖❖ Intelligent features including Auto Colour Balance
- ❖❖❖ Prints on paper weights up to 203gsm
- ❖❖❖ Duplex unit for double-sided printing (optional on C5300n)
- ❖❖❖ Optional second paper tray accessory increases paper capacity to 930 sheets



The C5300 are the ideal colour and mono printers for small workgroups.

OKI

C5300 COLOUR AND MONO PRINTER

PRODUCT SPECIFICATION

		C5300n	C5300dn
Order number		01099601	01103001
Speed & throughput	A4 Print speed	12ppm colour, 20ppm mono,	
	A4 OHP Colour	6ppm	
	Time to first print	14 seconds colour, 9 seconds mono	
	Warm-up time	95 seconds	
	Processor speed	400MHz	
Print quality	Resolution	600 x 1200 dpi	
	Enhancements	Automatic Colour Balance; Auto Registration; Toner Save mode	
Typefaces	Printer fonts	80 scalable PCL fonts, 1 bitmap font, 10 TrueType fonts, 136 Adobe Type 1 fonts, OCR A/B, USPS Barcode	
Printing process		Ultra compact Single Pass Digital LED electrophotographic page printer with four image drum cartridges	
Compatibility	Printer languages	PostScript®3 and PCL5c; Automatic emulation switching; Epson FX and IBM ProPrinter Dot Matrix emulations	
	Connectivity	USB(2.0), 10/100-TX Ethernet, IBM-Centro CEN36 IEEE 1284 Nibble, ECP	
	OS Compatibility	Windows 95 / 98 / 98 SE / ME / NT4 Workstation / NT4 Server / 2000 Workstation / 2000 Professional / 2000 Server / 2000 Advanced Server / XP Professional / XP Home / NT Terminal Server Edition / 2000 Terminal Server with Citrix Metaframe 1.8 or Citrix Metaframe XP 1.0. Mac OS 8.6 (or higher), Mac OS X (10.1 or higher), Variants of Unix and Linux via PPDs	
	Network & protocols	10/100BaseTX Ethernet Card with internal Web Server for printer and network card set-up and management. Includes POP3 and SMTP Mail client for submission of print jobs and for alerts. ALL major network protocols supported - TCP/IP, Netware, EtherTalk and NetBEUI. TCP/IP: ARP, RARP, IP, ICMP, TCP, UDP, LPR, FTP, TELNET, HTTP(PP), BOOTP, DHCP, SNMP, DNS, JetDirect protocols. Netware 3.x, 4.x, 5.x and 6 with full NDS and NDPS support: PServer, RPrinter, NDPS supported via dedicated OKI NDPS Gateway. EtherTalk: ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP. NetBEUI: SMB, NetBIOS.	
	Utilities	Print Control software*, PrintSuperVision, Oki Template Manager (Q2 2003); Storage Device Manager* : *Hard Disk Drive required	
Memory	RAM	64MB	128MB
	Max. RAM	320MB (optional 64MB, 128MB, 256MB DIMMs)	
	10GB Hard Disk Drive	Optional	
Paper-handling	Internal tray capacity (tray 1) and paper weight	300 sheets, 75—120gsm	
	Optional 2nd tray	530 sheets, 75—176gsm	
	Paper size (any tray)	A4, A5, B5, A6 (tray 1 only), Legal13, Legal13.5, Legal14, Letter, Executive	
	Multi-purpose tray	Max. capacity 100 sheets of 80 gsm paper. Paper sizes: A4, A5, B5, A6, C5, DL, Com-9, Com-10, Monarch, Custom Size (up to 1200mm length), Legal13, Legal13.5, Legal14, Letter, Executive	
	Multi-purpose paper weight	75—203gsm	
	Duplex	Optional	Standard
	Duplex paper weight	75—105gsm	
	Paper output	250 sheets face down, 100 sheets face up	
Operating conditions	Temperature/humidity (operating)	10°C — 32°C (17°C — 27°C recommended) / 20% — 80% RH (50% — 70% RH recommended)	
	Temperature/humidity (storage)	-14°C — 43°C, 10% — 90% RH	
Power requirements	Power supply	Single phase 220—240VAC, frequency 50Hz ± 2Hz	
	Power consumption	Typical 400W, Peak 850W, Idle 100W (average), Power save < 30W	
Noise level		Operating: 54dB(A), Standby: 40dB(A), Power save: 40dB(A)	
Dimensions (HxWxD)		342 x 400 x 528mm	
Weight		20kg approx (without consumables)	
Duty cycle	Max. printer duty	50,000 colour pages/month	
Warranty		Pan European 1 year on-site	
Supplies life	Toner	5,000 A4 pages @ 5% coverage per colour (printers are shipped with 1,500 A4 pages worth of each toner @ 5% coverage)	
	Drum	17,000 pages average life	
	Fuser	45,000 pages	
	Transport belt	50,000 pages @ average of 3 pages/job	

OKI

OKI Network Solutions
for a Global Society

OKI EUROPE, PART OF OKI ELECTRIC

OKI EUROPE LTD,
CENTRAL HOUSE, BALFOUR ROAD,
HOUNSLOW, MIDDLESEX, TW3 1HY,
UNITED KINGDOM
TEL: +44 (0)20 8219 2190
FAX: +44 (0)20 8219 2199

WWW.OKIEUROPE.COM

Only use genuine Oki Original consumables to ensure the best quality and performance from your hardware. Non Oki Original products may damage your printer's performance and invalidate your warranty. Specifications subject to change without notice. All trademarks acknowledged.



As an ENERGY STAR Partner, Oki Europe Ltd has determined that this product meets the ENERGY STAR guidelines for energy efficiency

© 2003 Oki Europe Ltd.